

Tooling on stock

	Standard stock material
	On order request

Wall thickness from 1,5-12,5 mm in some cases up to 20 mm.
CLR = Center Line Radius of bend

		Standard elbows					Special CLR						
		1,5D	2,0D	Spec.	Bauart 5	2,5D							
DN	Diameter [ØD]	CLR	CLR	CLR	CLR	CLR	CLR	CLR	CLR	CLR	CLR	CLR	
20	26,9	40		110		67		60	72	90	135	150	200
25	33,7	50	67	110		84		90	130	140	150	200	
32	42,4	63	85	110		106		120	150	160	180	200	
40	48,3	72	96	110		121		140	160	180	200	370	
50	60,3	90	120	125		151		160	180	240			
65	76,1	114	152		175	190		133	140	175	228	230	240
80	88,9	135	178		205	222		165	185	240	266	275	
100	114,3	171	228		270	286		305	342	420			
125	139,7	210	279		330	350		419					
150	168,3	253	336		390	421		500					
200	219,1	330	438		510								
250	273		546		650			820					
300	323,9				775								
350	355,6				850								
400	406,4				970								
500	508				1245								

Other tooling on stock

Diameter [ØD]	CLR	CLR	CLR	CLR	CLR
20	40	70	100		
21,3	150				
25	50	125			
28	50	56	75	160	
30	90				
32	80				
38	76	105			
108	162	216	324		
109	320				
110	220	330			
133	200	252	266	390	400
141,3	280				
159	239	477			
193,7	387				
325	850				