

Tooling on stock

	Standard stock material
	On order request

Wall thickness from 1,5-12,5 mm in some cases up to 20 mm.
CLR = Center Line Radius of bend

		Standard elbows					Special CLR					
		1,5D	2,0D	Spec.	Bauart 5	2,5D						
DN	Diameter [ØD]	CLR	CLR	CLR	CLR	CLR	CLR	CLR	CLR	CLR	CLR	CLR
20	26,9	40		110		67	60	72	90	135	150	200
25	33,7	50	67	110		84	90	130	140	150	200	
32	42,4	63	85	110		106	120	150	160	180	200	
40	48,3	72	96	110		121	140	160	180	200	370	
50	60,3	90	120	125		151	160	180	240			
65	76,1	114	152		175	190	133	140	175	228	230	240
80	88,9	135	178		205	222	165	185	240	266	275	
100	114,3	171	228		270	286	305	342	420			
125	139,7	210	279		330	350	419					
150	168,3	253	336		390	421	500					
200	219,1	330	438		510							
250	273		546		650		820					
300	323,9				775							
350	355,6				850							
400	406,4				970							
500	508				1245							

Other tooling on stock

Diameter [ØD]	CLR	CLR	CLR	CLR	CLR
20	40	70	100		
21,3	150				
25	50	125			
28	50	56	75	160	
30	90				
32	80				
38	76	105			
108	162	216	324		
109	320				
110	220	330			
133	200	252	266	390	400
141,3	280				
159	239	477			
193,7	387				
325	850				